



### SPECIFICATIONS

Current Rating: 2A AC,DC  
 Voltage Rating: 125V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

### Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
02P	2.00	6.60	4.60
03P	4.00	8.60	6.60
04P	6.00	10.60	8.60
05P	8.00	12.60	10.60
06P	10.00	14.60	12.60
07P	12.00	16.60	14.60
08P	14.00	18.60	16.60
09P	16.00	20.60	18.60
10P	18.00	22.60	20.60
11P	20.00	24.60	22.60
13P	24.00	28.60	26.60

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2012/12/26	SCALE 比例 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.25 .00 ± ANG. ± SIZE 紙張尺寸 A 4 REV. 版本 A	PART NAME 品名 MOLEX 2.00mm MALE HOUSING 1XXXP WHITE INSULATOR NYLON66 UL94-V0 (MOLEX 51005 Series) ROHS PART NO. 料號 H2040-XXPW1000R