



SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Circuit No.	Dimensions		
	A	B	C
02P	2.00	8.00	4.60
03P	4.00	10.00	6.60
04P	6.00	12.00	8.60
05P	8.00	14.00	10.60
06P	10.00	16.00	12.60
07P	12.00	18.00	14.60
08P	14.00	20.00	16.60
09P	16.00	22.00	18.60
10P	18.00	24.00	20.60
11P	20.00	26.00	22.60
13P	24.00	30.00	26.60

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖 <i>Helen</i>		.0 ± 0.25 .00 ± ANG. ±	
DATE 制表日	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 H2140-XXPW1000R
2012/12/26	PAGE 張數 1 OF 1	REV. 版本 A	