



SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Solder Tabs: Brass/Tin-plated
 Material: Nylon 6T,UL94V-0

P.C.B. LAYOUT

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
02	1.25	7.45
03	2.50	8.70
04	3.75	9.95
05	5.00	11.20
06	6.25	12.45
07	7.50	13.70
08	8.75	14.95
09	10.00	16.20
10	11.25	17.45
15	17.50	23.70
20	23.75	29.95
25	30.00	36.20
30	36.25	42.45

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 1.25mm WAFER SMT RIGHT ANGLE 1XXX TIN PLATED IVORY COLOR REEL PACKING (1ROLL=1000PCS) WITH POST ROHS LOW-LEAD
DWG. 製圖	Hedy	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	
DATE 制表日 2010/10/05		SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NO. 料號 W1353-XXPBTRI1R