



**SPECIFICATIONS**  
 Current Rating: 3A AC,DC  
 Voltage Rating: 500V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material: Nylon 66,UL94V-0  
 Pantone Color: 153C

**Ordering Information & Dimensions**

PIN	Dimensions	
	A	B
02P	2.50	5.00
03P	5.00	7.50
04P	7.50	10.00
05P	10.00	12.50
06P	12.50	15.00
07P	15.00	17.50
08P	17.50	20.00
09P	20.00	22.50
10P	22.50	25.00
11P	25.00	27.50
12P	27.50	30.00
13P	30.00	32.50
14P	32.50	35.00
15P	35.00	37.50

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>Angel</b>		TOLERANCE 容許公差 .0 ±0.25 .00 ±0.15 ANG. ±	PART NAME 品名 2.5mm WAFER XX P STRAIGHTTYPE TIN PLATED BROWN INSULATOR ROHS LOW-LEAD
DWG. 製圖 <b>Yumi</b>	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4 REV. 版次 A	PART NO. 料號 <b>W2605-XXPSTN00R</b>
DATE 制表日 <b>2008/07/22</b>			