



MATERIAL:

Contact:

phosphor Bronze thickness 0.17mm

Contact Plating: Sn-Cu plated 120u"~200u"

Insulator: PBT-4830 , UL 94V-0

SPECIFICATIONS:

Current Rating : 1A

Dielectric withstanding Voltage : 1000v RMS/minute

Insulator resistance : 5000 Megohms min.

Contact resistance : 20 milliohms initial

30 milliohms after test.

Operating temperatures : -55°c to 85°c

Insertion force : 340g (12 oz) max.per contact.

Withdrawal force : 80g (2.82 oz) min.per contact

CKT	A ±0.20	B ±0.20	C ±0.20	D ±0.20
40	35.56	33.78	17.70	15.24
42	37.34	35.56		
48	42.67	40.89		
52	46.23	44.45		
54	48.01	46.23		
56	49.78	48.01		
58	51.56	49.78		
60	53.34	51.56		
62	55.12	53.34		
64	56.90	55.12		

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
	APPD. 核准 HELEN	 TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 H.D. I.C. SOCKET 1.778mm XXP 0.6" WITH BAR TIN PLATING BLACK INSULATOR ROHS
	DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM SIZE. 紙張尺寸 A 4
	DATE 制表日 2017/10/20	PAGE 張數 1 / 1	REV. 版次 A
		PART NO. 料號 C0103-XXBYTB00R	