



BAR	No of contacts	Dim A	Dim B
no bar	24	27.94	30.48
no bar	28	33.02	35.56
no bar	32	38.10	40.64
no bar	40	48.26	50.80
with bar	20	22.86	25.40
with bar	24	27.94	20.32
with bar	28	33.02	35.56
with bar	32	38.10	40.64
with bar	36	43.18	45.72
with bar	40	48.26	50.80
with bar	42	50.80	53.34
with bar	48	58.42	60.96

**Technical Data:**

Material:

Insulator body(housing):PBT( black UL-94V0)

Pin: Brass,machined,C3602

Plating: Gold plated

2um/80u"nickel,0.025um/full gold-flashed

Electrical

Current rating: 3 Amps/contact max

Insulation resistance: > 1000MΩ at V=100 V

Operating: 60 Veff

Machanical:

Operating temperature: Gold plated:-55° C to + 125° C

Soldering temperature : +200 ° C, 10s max.

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2012/2/20	 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± .00 ± ANG. ± SIZE. 紙張尺寸 A4 REV. 版本 A	PART NAME 品名 2.54mm IC SOCKET MACHINED PIN STRAIGHT PIN ROW PITCH: 0.6" XXP ROHS PART NO. 料號 C0111-XXLNXB00R