



PCB Layout Diagram
Top View

- MAIN SPC:
1. Contact resistance: 30mΩ max.;
 2. Insulation resistance: 100MΩ min.;
 3. Withstand Voltage: 500V AC for one minute;
 4. Operation temperature: -40℃~+80℃;

TOLERANCE: UNLESS OTHERWISE SPECIFIED				
UNOVER1.5±0.1		1.5~10±0.2		OVER10.0±0.3
1	NEGATIVE PIN	1	QSn6.5-0.1 t=0.2	Au-Plated
2	POSITIVE PIN	1	QSn6.5-0.1 t=0.2	Au-Plated
3	HOUSING	1	PPA	BROWN
NO	PART NAME	QUNT'Y	MATERIAL	REMARK

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 BATTERY HOLDERS B66 FOR CR2032 GOLD PLATED BROWN INSULATOR ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0170-02LGN000R
DATE 製表日 2012/08/09	PAGE 張數 1 OF 1	REV. 版次 B	