



PCB Layout Diagram
Top View

NOTE:

1.MATERIAL:

- a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
 - b.CONTACT:PHOSPHOR BRONZE
(SURFACE PLATING: Ni100u")
- SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C ~ +85°C

UNLESS OTHERWISE
SPECIFIED TOLERANCES

DECIMALS:		ANGLES:	
X	: ±0.30	X	: ±1°
X.X	: ±0.25	X.X	: ±0.5°
X.XX	: ±0.20		
X.XXX	: ±0.10		

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	HELEN
DWG. 製圖	ABBY
DATE 制表日	2017/08/31

SCALE 比例	參考
UNIT 單位	MM
PAGE 張數	1 OF 1

TOLERANCE 容許公差	PART NAME 品名 BATTERY HOLDERS FOR CR2450 TIN PLATED BLACK COLOR ROHS	
SIZE. 紙張尺寸		A4
REV. 版次		A
PART NO. 料號		C0170-02UTB000R

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Ni-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.40MM	Ni-Plating
1	HOUSING	1	PBT	BLACK
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR