



④	COVER	1	LCP	WHITE
③	TERMINAL(-)	1	PHOSPHOR BRONZE, T=0.20mm	Sn Plating and Ni Under-Plating
②	TERMINAL(+)	1	PHOSPHOR BRONZE, T=0.20mm	Sn Plating and Ni Under-Plating
①	HOUSING	1	LCP	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

NOTE:

1.MATERIAL:

a.HOUSING:LCP UL94V-0  
b.CONTACT:PHOSPHOR BRONZE  
(SURFACE PLATING: Sn100u"-120u")  
SEE ORDERING INFORMATION

2.ELECTRIC:

a.CONTACT RESISTANCE: 30 MILLIOHMS MAX  
b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN  
c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL  
d.OPERATING TEMPERATURE: -25°C~ +85°C

PCB Layout Diagram  
Top View

APPD. 核准	SCALE 比例 参考	UNLESS OTHERWISE SPECIFIED TOLERANCES DECIMALS: X ±0.30 X 注1 X.X ±0.25 X.X ±0.5 X.XX ±0.20 X.XXX ±0.10	PART NAME 品名
			BATTERY HOLDERS FOR CR2450 SMT TYPE TIN PLATING BEIGE COLOR MATERIAL:LCP WITH COVER TRAY PACKING ROHS
DWG. 製圖	Betty	UNIT 單位	PART NO.
DATE 制表日	2019/01/07	PAGE 張數	料號 C0178-02DNTCYHR
		MM	1 OF 1
		REV. 版次	A

**RoHS Compliant**

**HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**