



PCB Layout Diagram
Top View

NOTE:

1.MATERIAL:

- a.HOUSING:LCP UL94V-0
 - b.CONTACT:PHOSPHOR BRONZE
(SURFACE PLATING: Sn100U"-120U")
- SEE ORDERING INFORMATION

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C~ +85°C

3	TERMINAL(-)	1	PHOSPHOR BRONZE, T=0.15mm	Sn-Plating
2	TERMINAL(+)	1	PHOSPHOR BRONZE, T=0.15mm	Sn-Plating
1	HOUSING	1	LCP	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
APPD. 核准		UNLESS OTHERWISE SPECIFIED TOLERANCES	PART NAME 品名	
DWG. 製圖	Betty	SCALE 比例 參考	BATTERY HOLDERS FOR CR1632	
DATE 制表日	2020/09/09	UNIT 單位 M M	SMT TYPE TIN PLATING	
		PAGE 張數 1 OF 1	BEIGE COLOR MATERIAL:LCP ROHS	
		REV. 版次 A	PART NO.	
			料號 C0180-02DNTCX0R	