



PCB LAYOUT

NOTE:

1. Shielded – 0.25mm THICKNESS BRASS C2680 H. PLATING NICKEL 20u” Min.
2. Housing – Standard Material LCP, Glass Filled Polyester UL94V-0 Standard Color Black.
3. RJ Terminal – Plastic: LCP UL94V-0, Standard Color Black. Pin: 0.35mm Thickness Phos-Bronze C5210 EH. Plating: Nickel 40u”~60u” for all and Sn 100% ,and Gold Plating.
4. Input Terminal – Plastic: LCP, Glass Filled, UL94V-0, Standard Color Black. Pin: 0.35mm SUS430. Plating: Nickel 40u”~60u” for all and Sn 100%.

**Industrial operation temp.: -40 degree C ~ + 85 degree C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE UNLESS OTHERWISE SPECIFIED .X± 0.38 X'± 2.0' .XX± 0.20 .X'± 1.0' .XXX± 0.10	PART NAME 品名 RJ45 TRANSFORMER PCB JACK 10/100/1000 UP LATCH W/ SHIELDED(BEHIND PEG 3.05mm) W/ TABS FLAT PIN W/ BI-COLOR LED LIGHT (GREEN & YELLOW) TRANSFORMER TYPE: TYPE 1 OPERATION TEMP.: -40°C ~ +85°C BLACK COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO.
DATE 制表日 2022/09/07	PAGE 張數 1 OF 2	REV. 版次 A	料號 C0241-88YXB411R

