



NOTE
 MATERIAL
 BODY&LATCH: NY66 RATED.
 CONTACTS:BRASS
 SHELL:SPCC
 LEG:BRASS
 RIVET:BRASS
 CONTACT PLATING: GOLD PLATING OVER NICKEL
 ELECTRICAL SPECIFICATION
 CURRENT RATING: 1.5A;
 VOLTAGE RATING: 40V;
 CONTACT RESISTANCE: 30mΩ MAX.
 INSULATION RESISTANCE:1000MΩ MIN 500V DC.
 DIELECTRIC WITHSTANDING VOLTAGE:500V AC
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -20°C~80°C.

PN:C0507-24FRCSW0YR	PN:C0507-24FRBSW0YR
NUT 4.75*11.80 L=4.80	NUT 4.75*11.80 L=4.80
LOCK NUT	ADD NUT

RoHS Compliant	玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	 TOLERANCE XX ±0.30 XX ±0.5 XXX ±0.20 XXX ±1 XXXX ±0.10 XXXX ±0.5	PART NAME 品名 DVI CONNECTOR DIGITAL 24 FEMALE RIGHT ANGLE TYPE SELECTIVE GOLD WHITE INSULATOR W/FIXED POST METAL SHELL:IRON METAL SHELL WITH RIMS ROHS
DWG. 製圖 ABBY	 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	PART NO. 料號 C0507-24FRXSW0YR
DATE 制表日 2017/03/03	REV. 版次 A	