



《HP · CN》

- **MATERIALS: (RoHS Compliant)**
 Housing: Plastic Thermoplastic P.B.T UL94V-0 Black
 Contacts: Phosphor Bronze Gold Selective Plated
 Front Shell: Steel Nickel Plated Over Copper

- **ELECTRICAL CHARACTERISTICS:**
 Contact Current Rating: 0.5 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: >500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -55°C ~ +85°C

- **MATERIALS: (RoHS Compliant)**
 Back Shell: Zinc Alloy Nickel Plated Over Copper
 Flat Screws: Steel Nickel Plated Over Copper
 Cable Clipper: Steel Nickel Plated Over Copper
 Spring Latches: Stainless Steel

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE 容許公差 0 ± .00 ± ANG. ±	PART NAME 品名 1.27mm SCSI II CEN. SOLDER CONNECTOR 36P MALE SPRING LATCHES(STAINLESS STEEL)METAL HOOD (ZINC PLATED NICKEL OVER COPPER) ENTRY HOLE SIZE: φ9mm SELECTIVE GOLD 5U" HP DB 36P MALE SOLDER ASSEMBLY ROHS
DWG. 製圖 KAREN	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. C0509-36MBLEZ0R 料號
DATE 制表日 2014/12/18	PAGE 張數 1 OF 1	REV. 版本 C	