



- MATERIALS: (RoHS Compliant)**  
 Housing And Cover: Plastic Thermoplastic  
 P.B.T UL94V-0 Black  
 Contacts: Phosphor Bronze Gold  
 Selective Plated  
 Boardlock: Brass Tin Plated  
 Over Copper
- ELECTRICAL CHARACTERISTICS:**  
 Contact Current Rating: 0.5 Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance:  $>500M\Omega/\text{Min}$   
 Contact Resistance:  $35m\Omega/\text{Max}$   
 Operation Temperature:  $-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		<b>TOLERANCE</b> 容許公差 $0 \pm 0.3$ $.00 \pm$ $ANG \pm$	<b>PART NAME 品名</b> SCSI-II D-SUB PCB 90° 1.27mm 68P FEMALE ALL PLASTIC WITHOUT SCREW HOLE WITHOUT FRONT LATCH WITH BOARDLOCK SELECTIVE GOLD 5U" PLATING BLACK COLOR ROHS
DWG. 製圖 <i>Helen</i>	<b>SCALE</b> 比例 參考	<b>SIZE</b> 紙張尺寸 A4	<b>PART NO.</b> 料號 C0519-68FCZOEBR
DATE 制表日 2014/6/19	<b>PAGE</b> 張數 1 OF 1	<b>REV.</b> 版本 A	