



● MATERIALS: (RoHS Compliant)

- Housing And Cover: Plastic Thermoplastic P.B.T UL94V-0 Black
- Contacts: Phosphor Bronze Gold Selective Plated
- Front Shell: Steel Nickel Plated Over Copper
- Bracket: Steel Nickel Plated Over Copper
- Boardlock: Brass Tin Plated Over Copper

● ELECTRICAL CHARACTERISTICS:

- Contact Current Rating: 0.5 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: >500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -55°C ~ +85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 SCSI-II CN PCB 90° 1.27mm 14P FEMALE THREAD INSERT M2.6 UNC METAL SHELL WITH BOARDLOCK SELECTIVE GOLD SU" PLATING BLACK COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0520-14FXZDEBR
DATE 制表日 2014/08/28	PAGE 張數 1 OF 1	REV. 版次 B	