



NOTES

- MATERIAL:**
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
- FINISH:**
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Area.
Shell:Nickel Plated.
Boardlock:Tin Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

- D-SUB
- Voltage: 250 VAC(RMS) Max.
- Current Rating: 3 Ampere per Contact
- Contact Resistance: 25 Milliohms Max.
- Insulation Resistance: 5000 Megohms Min.
- Dielectric Withstanding Voltage: 1000 VAC(RMS)
- Total Mating Force: 4.0 Kgf Max.
- Total Unmating Force: 1.0 Kgf Min.
- Operating Temperature: -55°C to +85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	D-SUB PCB STRAIGHT TYPE STAMPED PIN FRONT METAL-SHELL 9P MALE RIVET WITH 4-40 UNC BOARDLOCK NON ACCESSORIES BLACK INSULATOR ROHS
DATE 制表日	2014/11/07	UNIT 單位 M M	PART NO.
		PAGE 張數 1 OF 1	料號 C0543-09MDAXXBR
		REV. 版次 A	