



RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(F)

SPECIFICATIONS

1. D-SUB
- 1.1 Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 5000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 1000V AC(RMS)
- 1.6 Total Mating Force: 6.0 Kgf Max.
- 1.7 Total Unmating Force: 1.2 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

NOTES

1. MATERIAL:
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
Screw:Copper Alloy.
2. FINISH:
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Ared.
Shell:Nickel Plated.
Boardlock:Tin Plated.
Screw:Nickel Plated.
3. This Product is LEAD-FREE & RoHS Compliance Product.

		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
TOLERANCE XX ±0.25 .XXX ±0.13 X* ±2*		PART NAME 品名 D-SUB PCB STRAIGHT TYPE STAMPED PIN FRONT METAL-SHELL 15P FEMALE RIVET W/4-40 UNC BOARDLOCK FIX SCREWS(5.8x12) NICKEL SHELL SELECTIVE GOLD PLATING BLACK INSULATOR ROHS	
SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1		PART NO. 料號 C0543-15FDGNSBR	