



SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 3 Amperes.
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.
 Insulation Resistance: 5000 Megohms Minimum at DC 500V.
 Contact Resistance: 25 Milliohms Maximum.
 Operating Temperature: -55°C to +105°C.

RECOMMENDED P.C.B LAYOUT

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	SCALE 比例 参考	TOLERANCE 容許公差 X ±0.30 .XX ±0.25 XXX ±0.150 Ang. ±2°	PART NAME 品名 D-SUB PCB STRAIGHT TYPE STAMPED PIN FRONT METAL-SHELL 15P FEMALE RIVET W/4-40 UNC BOARDLOCK NON ACCESSORIES NICKEL+DIMPLE SHELL SELECTIVE GOLD PLATING BLACK INSULATOR ROHS
DWG. 製圖 Yumi		UNIT 單位 M M	PART NO. 料號 C0543-15MDAASBR
DATE 製表日 2010/12/21	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	REV. 版次 A