

Contact Resistance: 30mΩ max. at DC 100MA
 Insulator Resistance: 1000MΩ min. at DC 500V
 Current Rating: 1AP

Dielectric Withstanding
 Voltage: AC 1000V For 1 minute
 Operating Temperature: -55°C~+105°C
 Contact: Brass
 Housing: PBT & 30% Glass Fiber (UL 94V-0)

P. C. B LATOUT

4#40UNC
 BOARD LOCK

NO. OF CONTACT A $\pm 0.25/0.010$ B $0.123/0.005$ C 0.38 ± 0.015


09M	16.92/0.666	24.99/0.984	30.61/1.213
15M	25.25/0.994	33.32/1.312	39.14/1.541
25M	38.96/1.534	47.04/1.852	53.04/2.080
37M	55.42/2.182	62.50/2.500	69.32/2.729

RoHS
 Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SIZE. 紙張尺寸	D-SUB PCB RIGHT ANGLE 7.2mm STAMPED PIN XXP MALE WITH EMI RIVET W/BOARDLOCK W/O SCREWS GOLD FLASH PLATING BLACK INSULATOR ROHS
DATE 制表日	PAGE 張數	REV. 版本	PART NO. 料號
2015/3/3	1 OF 1	A	C0550-XXABA(A,B)GBR

Helen



SCALE 比例 參考

UNIT 單位 MM

PAGE 張數 1 OF 1



TOLERANCE 容許公差
 0.00 ± 0.25
 ANG. ±

SIZE. 紙張尺寸 A4

REV. 版本 A

PART NAME 品名
 D-SUB PCB RIGHT ANGLE 7.2mm STAMPED
 PIN XXP MALE WITH EMI RIVET W/BOARDLOCK
 W/O SCREWS
 GOLD FLASH PLATING BLACK INSULATOR ROHS

PART NO.
 料號 C0550-XXABA(A,B)GBR