



MATERIAL

Insulator :PBT+30% Glass Fiber (UL94V-0)
 Contact :Phosphor Bronze or Brass (Standard is Brass)
 Contact Plated:Gold over Nickel
 Shell : Nickel plated or Tin plated

SPECIFICATION

Current Rating :3Amps
 Insulator Resistance :1000MΩ Min. at 500V DC
 Withstanding Voltage :500V AC/minute
 Operating Temperature:-40°C to +105°C

DIM	A	B	C	D	E	F	G	H	I	J
15	16.90	25.00	30.80	8.40	12.50	7.039	2.286	1.981	10.70	19.30
26	25.30	33.30	39.10	8.40	12.50	6.871	2.286	1.981	10.70	27.50
44	39.00	47.00	53.00	8.40	12.50	6.863	2.286	1.981	10.70	41.30
62	55.40	63.50	69.30	8.40	12.50	6.998	2.413	1.981	10.70	57.70
78	52.90	61.10	66.90	11.20	15.40	7.627	2.413	2.083	13.60	55.30

APPD. 核准 DWG. 製圖 DATE 制表日 2016/07/25	Betty	TOLERANCE 容許公差 .0 ±0.30 .00 ±0.25 ANG. ±2°	PART NAME 品名 H.D. D-SUB SOLDER TYPE STAMPED PIN XXP MALE THROUGH HOLE(TIN OR NICKEL) SHELL+DIMPLE RoHS

RoHS Compliant **HSM** 玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1
 SIZE 紙張尺寸 A4
 REV. 版次 C