



MATERIALS AND FINISH
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,
 UL 94V-0 RATED, BLACK COLOR
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH
 COAXIAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

ELECTRICAL CHARACTERISTICS
 SIGNAL CONTACT CURRENT RATING : 5.0 AMPS
 SIGNAL CONTACT RESISTANCE : 2.7 mΩ MAX.
 COAXIAL CONTACT IMPEDANCE : 50 Ω
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC FOR 1 MINUTE
 INSULATION RESISTANCE : 10⁷MΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 D-SUB COAXIAL SOLDER TYPE 25W3 MALE 50 OHMS RIVET 4-40UNC 4.0mm OPEN NUTS ON READ SHELL TIN SHELL+DIMPLE WITH SIGNAL CONTACT GOLD PLATING BLACK INSULATOR ROHS
DWG. 製圖 BETTY		UNIT 單位 MM	PART NO. 料號 C0590-HMADA0GBR
DATE 制表日 2011/03/07	PAGE 張數 1 OF 1	REV. 版次 A	