



Specification

- * Electrical Characteristics :
 - Current Rating: 0.5A AC/DC Max.
 - Dielectric Withstanding Voltage: 250V AC/DC
 - Insulation Resistance: 500M ohms Min.
 - Contact Resistance: 100m ohms Max.
- * Mechanical Characteristics:
 - Mating Cycles: 5000 Insertions.
- * Environmental :
 - Operating Temperature: -40°C to +85°C.
- * Material:
 - 1.Housing:HI-Temp plastic UL 94V-0 Rated.
 - 2.Contact:Copper Alloy.
 - 3.Shell:Stainless Steel SUS 304,t=0.20mm.
- * Plating :
 - Terminal:
 - Contact area: Gold Flash Plated Over 40u"

Nickel.

- Solder area: 80u" Tin Plated Over 40u" Nickel.
- Under plate: 40u"Min. Nickel.
- Shell:
 - 30u"Min. Nickel Plated Over All,
 - Solder Area: Gold Flash.

PIN NO.	DESCRIPTION
P1#	C1:VCC
P2#	C5:GND
P3#	C2:RST
P4#	C6:VPP
P5#	C3:CLK
P6#	C7:I/O
P7#	CD SW LOWER
P8#	CD SW UPPER



RECOMMENDED PCB LAYOUT(TOP VIEW)
 GENERAL TOLERANCES:±0.05
 SOLDER AREA

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 2020/05/29	Betty	DIMENSION IN mm (inch) TOLERANCE UNLESS OTHERWISE SPECIFIED .XX±0.3 .X".±.01" .XX±0.2 .X".±.005" .XXX±0.1 .XX".±.002"	PART NAME 品名 SIM CARD PUSH-PUSH TYPE SMT TYPE 6P WITH POST & WITH SWITCH BLACK COLOR TAPE & REEL PACKING ROHS
UNIT 單位 M M	SCALE 比例 參考	SIZE 紙張尺寸 A 4	PART NO. 料號 C0621-06YXBR02R
PAGE 張數 1 OF 1	REV. 版次 A		