



- NOTES:
- General Characteristics  
Mounting System:SMT  
Durability:3,000 cycles min.
  - Material and Finish:  
Insulation material:High Temperature Plastic (UL94V-0)  
Contact material:Copper Alloy
  - Electrical Characteristics  
Contact resistance:100 mΩ max.  
Insulation resistance:>1000 megaohms /500 VDC
  - Environmental Characteristics  
Operating temperature:-40°C~+85°C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		TOLERANCE .X±0.30	PART NAME 品名 SIM CARD CONNECTOR PUSH-PUSH TYPE H=1.8mm 6P
DWG. 製圖 <b>Hedy</b>	SCALE 比例 參考	.XX±0.20 .XXX±0.10	SMT TYPE SELECTIVE GOLD 5U" PLATING WITHOUT POST & WITHOUT SWITCH BLACK COLOR REEL PACKING ROHS
DATE 制表日 2015/08/21	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0647-06NEBR00R
PAGE 張數 1 / 1	REV. 版次 A		