



- NOTES:
- General Characteristics  
Mounting System: SMT  
Durability: 3,000 cycles min.
  - Material and Finish:  
Insulation material: High Temperature Plastic (UL94V-0)  
Contact material: Copper Alloy  
Contact Finish: See Order Information Selectivity.
  - Electrical Characteristics  
Number of contacts: 6 Position & 8 Position  
Contact resistance: 50 mΩ typical, 100 mΩ max.  
Insulation resistance: >1000 megaohms / 500 VDC  
Operation: Normally open.
  - Environmental Characteristics  
Operating temperature: -40°C ~ +85°C  
Operating humidity: 10% ~ 95%RH  
Storage temperature: -40°C, +85°C  
Storage humidity: 10% ~ 95%RH  
Thermal shock: -40°C ~ +85°C, 5 cycles  
Damp Heat: 40°C, 90%RH, 10 days.  
Salt-mist: 35°C, 5%, NaCl, 24 Hrs.

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SIZE 紙張尺寸	SIM CARD CONNECTOR PUSH-PUSH TYPE H=1.8mm 8P SMT TYPE SELECTIVE GOLD 5U" PLATING WITH POST & WITH SWITCH BLACK COLOR REEL PACKING ROHS
DATE 制表日	PAGE 張數	REV. 版次	PART NO. 料號
2020/11/10	1 OF 1	A	C0647-08YEBR00R

Betty