



NOTES 1:
 UL Standard :
 1. Rating: 300V 15A
 2. Insulation Withstands Voltage:
 AC 2000V at 1 minute
 3. Using Temperature Range:
 -40°C~+115°C
 IEC Standard :
 Rating: 600V 18A
 2. Rate Impulse Voltage: 4000V
 3. Insulation Resistance:
 500MΩ or more at DC500V
 4. Material Group : I
 5. Pollution Degree : 2
 6. Overvoltage Category: II
 7. Using Temperature Range:
 -40°C~+110°C

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2		0 to 10
over 100 to 150	0.3	0.3	over 10
over 150	0.5		0.3
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44
90<U<=115	±0.44	over 90~115	±0.55
115<U<=150	±0.55	over 115~150	±0.70
150<U<=200	±0.70	over 150~200	±0.85

ITEM	NAME OF PART	MATERIAL	NOTES
2	SOLDER PIN	COPPER ALLOY	TIN PLATED
1	HOUSING	PA	UL94-V0 GREEN

P.C.B. LAYOUT(REF)

P	2	3	4	5	6	7	8	9	10	11	12	
U	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	
P	13	14	15	16	17	18	19	20	21	22	23	24
U	60.00	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00

RoHS Compliant

HSM 玄茂科技股份有限公司

HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	BETTY	SCALE 比例	参考	TOLERANCE 容許公差	.0 ±	PART NAME 品名 5.0mm TERMINAL BLOCK PCB TYPE XXP 90° GREEN COLOR FOUR COVERS & WITHOUT SCREWS ROHS
DWG. 製圖	KAREN	UNIT 單位	MM	ANG. ±	SIZE 紙張尺寸	
DATE 制表日	2015/08/14	PAGE 張數	1 OF 1	REV. 版本	B	PART NO. 料號 C0906-XXRTEC00R