



SPECIFICATIONS

- ① Housing Material: Polyamide 66(UL94V-0), Green
- ② Screw: M2.6 Yellow Zinc Plated Steel
- ③ Terminals: Tin Plated Brass
- ④ Contact: Stainless Strip Steel

Screws Torque: 2 In-Lb

Wire Range: 16~22 AWG

Rated: 10 Amperes.AC250V

Operation Temperature: $-55^{\circ}\text{C} \sim +100^{\circ}\text{C}$

Insulation withstands volt: AC2000V min

Insulation resistance: $>1000\text{M}\Omega$ or more at DC500V

Tolerance ± 0.5

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	10.5	15.5	20.5	25.5	30.5	35.5	40.5	45.5	50.5	55.5	60.5	65.5	70.5	75.5
B	5	10	15	20	25	30	35	40	45	50	55	60	65	70
POLE	16	17	18	19	20	21	22	23	24	25	26			
A	80.5	85.5	90.5	95.5	100.5	105.5	110.5	115.5	120.5	125.5	130.5			
B	75	80	85	90	95	100	105	110	115	120	125			

RoHS Compliant		HSM 玄茂科技股份有限公司	
		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	KAREN	SCALE 比例 參考	5.0mm TERMINAL BLOCK XXP STRAIGHT H:11mm SUITABLE FOR 16~22AWG ROHS
DATE 制表日	2015/08/14	UNIT 單位	PART NO. 料號
		PAGE 張數	C0907-XXSUTX00R
		1 OF 1	