



NOTES 1:
 UL Standard :
 1. Rating: 300V 15A
 2. Insulation Withstands Voltage:
 AC 2000V at 1 minute
 3. Using Temperature Range:
 -40°C~+115°C

IEC Standard :
 1. Rating: 600V 18A
 2. Rate Impulse Voltage: 4000V
 3. Insulation Resistance:
 500MΩ or more at DC500V
 4. Material Group : I
 5. Pollution Degree : 2
 6. Overvoltage Category: II
 7. Using Temperature Range:
 -40°C~+110°C

NOTE 2:
 1. RoHS Compliance.

P	4	6	8	10	12	14	16	18	20	22
U	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00
V	12.00	17.00	22.00	27.00	32.00	37.00	42.00	47.00	52.00	57.00
P	24	26	28	30	32	34	36	38	40	
U	55.00	60.00	65.00	70.00	75.00	80.00	85.00	90.00	95.00	
V	62.00	67.00	72.00	77.00	82.00	87.00	92.00	97.00	102.00	

3	SOLDER PIN	COPPER ALLOY	Tin Plated
2	END COVER	PA66	UL94-V0 GREEN
1	HOUSING	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
 DWG. 製圖
 DATE 制表日
 2021/07/14

SCALE 比例 參考
 UNIT 單位 M M
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 .0 ±
 .00 ±
 ANG. ±

PART NAME 品名
 5.0MM HEADER FOR PLUGGABLE TERMINAL
 BLOCKS DOUBLE-DECKED H=22.0MM 2XXXPIN
 180° WITHOUT SCREW HOLE
 TIN PLATING GREEN INSULATOR ROHS

PART NO.
 料號 C0917-XXSNTE00R