



- NOTES:
1. Rating: 300V 10A
PITCH: 5.08mm
 2. Insulation Withstands Voltage:
AC2000 V at 1 minute.
 3. Insulation Resistance:
500MΩ or more at DC500V
 4. Using Temperature Range:
-40°C~+105°C
 5. Suitable Electric Wire: AWG 26~12
 6. RoHS Compliance

5	LEVER	POM	ORANGE
4	CLAMP2	STAINLESS STEEL	
3	COVER	PA66	UL94-V0 GREEN
2	CLAMP1	BRONZE	Tin Plated
1	HOUSING	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Normal Geometric Tolerancing			
	-	//	⊥
0 to 100	0.2		0 to 10 0.2
over 100 to 150	0.3	0.3	over 10 0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44
90<U<=115	±0.44	over 90~115	±0.55
115<U<=150	±0.55	over 115~150	±0.70

P	2	3	4	5	6	7	8	9	10	11	12	13
U	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96
V	10.26	15.34	20.42	25.50	30.58	35.66	40.74	45.82	50.90	55.98	61.06	66.14
P	14	15	16	17	18	19	20	21	22	23	24	
U	66.04	71.12	76.20	81.28	86.36	91.44	96.52	101.6	106.68	111.76	116.84	
V	71.22	76.30	81.38	86.46	91.54	96.62	101.7	106.78	111.86	116.94	122.02	

RoHS Compliant

HSM 玄茂科技股份有限公司

HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	Betty		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty		SCALE 比例 參考	5.08mm TERMINAL BLOCK PLUGGABLE TYPE XXPIN SUITABLE FOR 12~26AWG NICKEL PLATED GREEN INSULATOR ROHS
DATE 制表日	2013/01/23	UNIT 單位	SIZE 紙張尺寸	PART NO. 料號
		PAGE 張數	REV. 版次	C0937-XXA2NE000R
		1 OF 1	A 4	