


P	4	6	8	10	12	14	16	18	20	22	24
A	3.50	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50
B	7.04	10.54	14.04	17.54	21.04	24.54	28.04	31.54	35.04	38.54	42.04
P	26	28	30	32	34	36	38	40	42	44	
A	42.00	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	
B	45.54	49.04	52.54	56.04	59.54	63.04	66.54	70.04	73.54	77.04	

NOTES:

- Rating: 150V 8A (UL)
320V 10A (VDE)
PITCH: 3.50mm
- Insulation Withstands Voltage:
AC 2000V at 1 minute
- Insulation Resistance:
500MΩ or more at DC500V
- Operating Temperature Range:
-40°C ~ +120°C
- Suitable Electric Wire:
UL: 28 ~ 16 AWG
VDE: 0.2mm² ~ 1.0mm²
Strip length: 8~9mm



ITEM	NAME OF PART	MATERIAL	NOTES
5	LEVER	POM	
4	S-CAGE	STAINLESS STEEL	
3	CLAMP	COPPER ALLOY	Tin PLATED
2	COVER	PA66	UL94-V0
1	HOUSING	PA66	UL94-V0

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 3.5mm TERMINAL BLOCKS DOUBLE-DECKED TYPE 2XXXP WIRE CAGE TYPE TIN PLATING FOR 16~28AWG GREEN INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C0940-XXA4TE00R
DATE 制表日 2023/03/20	PAGE 張數 1 OF 1	REV. 版次 B	