



SPECIFICATIONS

- ① Housing Material: Polyamide 66(UL94V-0), Black
- ② Screw: M3.0 Nickel Plated Steel
- ③ Terminals: Tin Plated Brass
- ④ Cover: PC Transparent

Screws Torque: 7 In-Lb
 Wire Range: 18~22 AWG
 Rated: 10 Amperes.AC250V
 Operation Temperature: -55°C~+110°C
 Insulation withstands volt: AC2000V min
 Insulation resistance: >1000MΩ or more at DC500V

Tolerance ± 0.5

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
A	26.55	32.9	39.25	45.6	51.95	58.3	64.65	71	77.35	83.7	90.05	96.4	102.75	109.1	
B	19.05	25.4	31.75	38.1	44.45	50.8	57.15	63.5	69.85	76.2	82.55	88.9	95.25	101.6	
POLE	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A	115.45	121.8	128.15	134.5	140.85	147.2	153.55	159.9	166.25	172.6	179	185.3	191.7	198	204.35
B	107.95	114.3	120.65	127	133.35	139.7	146.05	152.4	158.75	165.1	171.5	177.8	184.2	190.5	196.9

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 BETTY		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 6.35mm Barrier Terminal Block H=15mm XXPin Solder Pin Type Suitable For 18~22Awg With or without Cover(Transparent Color) Tin Plating Black Color ROHS
DWG. 製圖 KAREN	SCALE 比例 參考	UNIT 單位 MM	SIZE 紙張尺寸 A4
DATE 制表日 2015/08/05	PAGE 張數 1 OF 1	REV. 版本 A	PART NO. 料號 C0942-XXCDT (Y,N)B0R