



MATERIAL
 HOUSING : THERMOPLASTIC UL94V-0
 CONTACT : COPPER ALLOYS

SPECIFICATION
 CURRENT: 1A
 OPERATING TEMPERATURE: -55°C TO +105°C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN
 DIELECTRIC STRENGTH : 1000 VAC MIN
 DURABILITY : 100 CYCLES
 RETENTION FOREC : 700g MIN

FINISH
 CONTACT PLATING SEE ORDER INFORMATION

RECOMMENDED P.C.B LAYOUT

CONTACTS	1X21
1X2	1X22
1X3	1X23
1X4	1X24
1X5	1X25
1X6	1X26
1X7	1X27
1X8	1X28
1X9	1X29
1X10	1X30
1X11	1X31
1X12	1X32
1X13	1X33
1X14	1X34
1X15	1X35
1X16	1X36
1X17	1X37
1X18	1X38
1X19	1X39
1X20	1X40

APPD. 核准 BETTY DWG. 製圖 BETTY DATE 制表日 2013/04/24	RoHS Compliant	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE .0=±0.38 .00=±0.25 ANG=±5° SIZE 紙張尺寸 A 4 REV. 版次 A	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.
	PART NAME 品名 1.27mm PIN HEADER SINGLE ROW DUAL INSULATOR 1X17P 180° H:1.5mm FULL GOLD PLATING (C=6.0mm D=2.6mm E=3.0mm) MATERIAL:NYLON 6T ROHS			
	PART NO. 料號 C1173-XXESGCA0R			

C=6mm D=2.6mm E=3mm F=11.6mm