



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Copper Alloy
 Standard: Brass
 Insulator Material: High Temperature Polyester,UL 94V-0

Standard:Gold Flash all over

Recommended P.C. Board Hole Layout

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2016/04/14	TOLERANCE 容許公差 .X .XX .XXX ±0.3 ±0.20 ±0.100 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	PART NAME 品名 1.27mm PIN HEADER SINGLE ROW HORIZONTAL SMT TYPE 1XXXP H=1.5mm GOLD FLASH PLATING (C=3.55mm D=2.3mm E=1.27mm) WITHOUT LOCATING PEG BOX PACKING ROHS PART NO. 料號 C1176-XXADGATDR	