



CONTACTS	2X26
2X2	2X27
2X3	2X28
2X4	2X29
2X5	2X30
2X6	2X31
2X7	2X32
2X8	2X33
2X9	2X34
2X10	2X35
2X11	2X36
2X12	2X37
2X13	2X38
2X14	2X39
2X15	2X40
2X16	2X41
2X17	2X42
2X18	2X43
2X19	2X44
2X20	2X45
2X21	2X46
2X22	2X47
2X23	2X48
2X24	2X49
2X25	2X50

**MATERIAL**  
 HOUSING : THERMOPLASTIC UL94V-0 (NYLON 6T)  
 CONTACT : COPPER ALLOYS

**SPECIFICATION**  
 CURRENT: 1A  
 OPERATING TEMPERATURE: -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN  
 DIELECTRIC STRENGTH : 1000 VAC MIN  
 MAX PROCESSING TEMP:  
 260°C FOR 5~8 SECONDS

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考	一般公差 (TOLERANCE) 0=±0.38 .00=±0.25 ANG=±5°	PART NAME 品名 1.27X2.54mm PIN HEADER DUAL ROW DUAL INSULATOR 2XXXP STRAIGHT TYPE H=2.5mm GOLD FLASH PLATING (C=2.5mm D=3.5mm E=20.8mm T/L=26.8mm) MATERIAL: NYLON 6T ROHS
DWG. 製圖 BETTY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C1270-XXFSGSA0R
DATE 製表日 2011/07/19	PAGE 張數 1 OF 1	REV. 版次 A	