



MATERIAL
 HOUSING : THERMOPLASTIC UL94V-0
 CONTACT : COPPER ALLOYS

SPECIFICATION
 CURRENT: 3A
 OPERATING TEMPERATURE: -55°C TO +105°C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE : 1000 MEGAOHMS MIN
 WITHSTANDING VOLTAGE : AC 1000V RMS

CONTACTS	2X21
2X2	2X22
2X3	2X23
2X4	2X24
2X5	2X25
2X6	2X26
2X7	2X27
2X8	2X28
2X9	2X29
2X10	2X30
2X11	2X31
2X12	2X32
2X13	2X33
2X14	2X34
2X15	2X35
2X16	2X36
2X17	2X37
2X18	2X38
2X19	2X39
2X20	2X40

RECOMMENDED P.C.B LAYOUT

C=2.85mm D=7.5mm E=3.5mm

APPD. 核准 DWG. 製圖 BETTY DATE 制表日 2015/06/25	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE .0=±0.38 .00=±0.25 ANG=±5° SIZE. 紙張尺寸 A 4 REV. 版次 A	RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.
			PART NAME 品名 1.27X1.27mm DUAL ROWS SINGLE INSULATOR PIN HEADER H:2.5mm 2XXXP SMT TYPE (C=2.85mm D=7.5mm E=3.5mm) ROHS	
			PART NO. 料號 C1272-XXBDXFA0R	