



RECOMMENDED P.C.B LAYOUT

D: 5.5 mm C: 5.8 mm E: 8.2 mm T/L= 15 mm

CONTACTS	2X21
2X2	2X22
2X3	2X23
2X4	2X24
2X5	2X25
2X6	2X26
2X7	2X27
2X8	2X28
2X9	2X29
2X10	2X30
2X11	2X31
2X12	2X32
2X13	2X33
2X14	2X34
2X15	2X35
2X16	2X36
2X17	2X37
2X18	2X38
2X19	2X39
2X20	2X40

MATERIAL
HOUSING : THERMOPLASTIC UL94V-0
CONTACT : COPPER ALLOYS

SPECIFICATION
CURRENT: 3A
OPERATING TEMPERATURE: -55°C TO +105°C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE : 1000 MEGAOHMS MIN
WITHSTANDING VOLTAGE : AC 1000V RMS

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准
DWG.
製圖
DATE
制表日
2013/03/22

SCALE
比例
UNIT
單位
PAGE
張數
1 OF 1

TOLERANCE
容許公差
0 ± 0.38
.00 ± 0.25
ANG. ±
SIZE
紙張尺寸
A4
REV.
版本
A
PART NAME 品名
1.27X1.27mm PIN HEADER H=2.5mm DUAL ROW DUAL
INSULATOR 2XXP SMT TYPE GOLD FLASH PLATING
(C=5.8mm D=5.5mm E=8.2mm) TUBE PACKING ROHS
PART NO.
料號 C1272-XXFDGHATR