



CONTACTS	
2X3	2X27
2X4	2X28
2X5	2X29
2X6	2X30
2X7	2X31
2X8	2X32
2X9	2X33
2X10	2X34
2X11	2X35
2X12	2X36
2X13	2X37
2X14	2X38
2X15	2X39
2X16	2X40
2X17	2X41
2X18	2X42
2X19	2X43
2X20	2X44
2X21	2X45
2X22	2X46
2X23	2X47
2X24	2X48
2X25	2X49
2X26	2X50

**MATERIAL**  
 HOUSING : NYLON 6T,UL94V-0  
 CONTACT : COPPER ALLOYS  
 PLATED : GOLD-FLASH  
 COLOR : BLACK

**SPECIFICATION**  
 CURRENT: 1A  
 OPERATING TEMPERATURE: -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN  
 DIELECTRIC STRENGTH : 1000 VA

RoHS  
Compliant

**HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准		TOLERANCE .0=±0.38 .00=±0.25 ANG=±5°
DWG. 製圖		SCALE 比例 參考
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸
2017/03/01	PAGE 張數	REV. 版次
Betty	M M	A 4
	1 OF 1	A

**PART NAME 品名**  
 1.27X1.27mm DUAL ROWS SINGE INSULATOR  
 PIN HEADER H:2.0mm 2XXXP SMT TYPE  
 GOLD FLASH PLATING WITH LOCATING PEG  
 (C=3.0mm D=5.5mm E=3.0mm) ROHS

**PART NO.**  
 料號 C1274-XXBDGCAXR