



CONTACTS	2X21
2X2	2X22
2X3	2X23
2X4	2X24
2X5	2X25
2X6	2X26
2X7	2X27
2X8	2X28
2X9	2X29
2X10	2X30
2X11	2X31
2X12	2X32
2X13	2X33
2X14	2X34
2X15	2X35
2X16	2X36
2X17	2X37
2X18	2X38
2X19	2X39
2X20	2X40

C: 3.00 mm D: 2.60 mm E: 1.20 mm

MATERIAL  
 HOUSING : THERMOPLASTIC UL94V-0  
 CONTACT : COPPER ALLOYS

SPECIFICATION  
 CURRENT: 1A  
 OPERATING TEMPERATURE: -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN  
 DIELECTRIC STRENGTH : 1000 VAC MIN  
 DURABILITY : 100 CYCLES  
 RETENTION FORCE : 700g MIN

FINISH  
 CONTACT PLATING SEE ORDER INFORMATION

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 HELEN DATE 創表日 2010/9/2	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE .0=±0.38 .00=±0.25 ANG=±5° SIZE 紙張尺寸 A4 REV. 版本 A	PART NAME 品名 1.27X1.27 DUAL ROW PIN HEADER 2XXP 90° H=1.5mm C=3mm D=2.6mm E=1.2mm ROHS LOW-LEAD PART NO. 料號 C1280-XXBRXAR0R