



RECOMMENDED P.C.B LAYOUT



T/L: 5.50 mm C: 1.80 mm D: 2.20 mm

CONTACTS	2X26
2X2	2X27
2X3	2X28
2X4	2X29
2X5	2X30
2X6	2X31
2X7	2X32
2X8	2X33
2X9	2X34
2X10	2X35
2X11	2X36
2X12	2X37
2X13	2X38
2X14	2X39
2X15	2X40
2X16	2X41
2X17	2X42
2X18	2X43
2X19	2X44
2X20	2X45
2X21	2X46
2X22	2X47
2X23	2X48
2X24	2X49
2X25	2X50

MATERIAL
 HOUSING : THERMOPLASTIC UL94V-0 (NYLON 6T)
 CONTACT : COPPER ALLOYS

SPECIFICATION
 CURRENT: 1A
 OPERATING TEMPERATURE: -40°C TO +105°C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN
 WITHSTANDING VOLTAGE : AC 500V RMS

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考	一般公差 (TOLERANCE) 0=±0.38 00=±0.25 ANG=±5°	PART NAME 品名 1.0mm PIN HEADER DUAL ROW H=1.5mm STRAIGHT TYPE 2XXXP (C=1.8mm D=2.2mm) ROHS
DWG. 製圖 BETTY	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C1801-XXBSXAS0R
DATE 制表日 2011/11/07	PAGE 張數 1 OF 1	REV. 版次 A	