



MATERIAL
HOUSING : NYLON 6T,UL94V-0
CONTACT : COPPER ALLOYS
PLATED : GOLD-FLASH
COLOR : BLACK

SPECIFICATION
CURRENT : 1A
OPERATING TEMPERAURE : -40 °C TO +105 °C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE: 5000 MEGAOHMS MIN
WITHSTAND VOLTAGE : 500 V AC MIN

CONTACTS	
1×3	1×27
1×4	1×28
1×5	1×29
1×6	1×30
1×7	1×31
1×8	1×32
1×9	1×33
1×10	1×34
1×11	1×35
1×12	1×36
1×13	1×37
1×14	1×38
1×15	1×39
1×16	1×40
1×17	1×41
1×18	1×42
1×19	1×43
1×20	1×44
1×21	1×45
1×22	1×46
1×23	1×47
1×24	1×48
1×25	1×49
1×26	1×50

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	TOLERANCE .0=±0.38 .00=±0.25 ANG=±5°	PART NAME 品名	
DWG. 製圖		SCALE 比例 參考	2.54mm PIN HERADER Z TYPE SINGLE ROW H=1.5mm (W=2.5mm) 1XXXP GOLD FLASH PLATING (C=3.75mm D=3.75mm E=7.0mm) ROHS
DATE 制表日	UNIT 單位 M M	SIZE 紙張尺寸	A 4
2015/06/04	PAGE 張數 1 OF 1	REV. 版次	A
		PART NO.	C2110-XXAGBA00R
		料號	C2110-XXAGBA00R