



**MATERIAL**

Insulator : PBT+30% Glass fiber  
 Contact Pin : Brass

**SPECIFICATION**

Current Rate : 3 AMP  
 Insulation Resistance : 100000MΩMin. at DC 500V  
 Contact Resistance : 20mΩMax. at DC 100mA  
 Dielectric Voltage : 750V AC for one minute  
 Temperature Range : -55°~105° C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>HELEN</b>		<b>TOLERANCE 容許公差</b> .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	<b>PART NAME 品名</b> 2.54mm MINI JUMPER 2P H:6.5mm CLOSE COVER ROHS LOW-LEAD
DWG. 製圖 <b>ABBY</b>	<b>SCALE 比例 參考</b> UNIT 單位 <b>MM</b>	<b>SIZE 紙張尺寸</b> <b>A4</b>	<b>PART NO. 料號</b> <b>C2700-02ABXX00R</b>
DATE 制表日 2011/03/23	<b>PAGE 張數</b> 1 OF 1	<b>REV. 版本</b> <b>A</b>	