



CIRCUIT	DIM "A"	DIM "B"
2	2.54 (0.100)	5.08 (0.200)
3	5.08 (0.200)	7.62 (0.300)
4	7.62 (0.300)	10.16 (0.400)
5	10.16 (0.400)	12.70 (0.500)
6	12.70 (0.500)	15.24 (0.600)
7	15.24 (0.600)	17.78 (0.700)
8	17.78 (0.700)	20.32 (0.800)
9	20.32 (0.800)	22.86 (0.900)
10	22.86 (0.900)	25.40 (1.000)
2X13	30.48 (1.200)	33.02 (1.300)

**FEATURES**  
 Double tuning fork type contact quarantees high reliability.  
 2.54MM pitch Low-Profile mini type Match to 0.64mm sq. posts.

**MATERIAL**  
 .Dinsulator.D.D.D.D.D.D.D.D.D.D.D30FH Glass Filled P.B.T.(UL 94v-0)  
 .DContact.D.D.D.D.D.D.D.D.D.D.D.D.D.D.D.DGold Plated  
 .DTerminal.D.D.D.D.D.D.D.D.D.D.D.D.D.D.D.DC2680

**SPECIFICATIONS**  
 .DCurrent Rating: 3 amperes MAX  
 .DConcact Resistance: 30mΩ MAX  
 .DInsuation Resistance: 1000 megohms MAX  
 .DDielectric Withstanding Voltage: AC 650 volts RMS at sea leve

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b>		<b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名		
DWG. 製圖 <i>Helen</i>		0 ± 0.35 .00 ± 0.25 ANG. ± 5°	2.54mm MULTI JUMPER ??P(2X??) GOLD PLATING BLACK COLOR ROHS		
DATE 制表日	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO.		
2020/9/23	PAGE 張數 1 OF 1	REV. 版本 A	料號 C2720-XXADGB00R		