


W/O Plugged Key



W/ Plugged Key

Specifications:
 Current Rating:1.0 Amp
 Contact resistance:20m Ohm Max. at 6V DC 0.3A
 Insulator resistance:1000M ohm min. at 500V DC
 Withstanding Voltage:500V AC/Minute
 Operating Temperature Range:-55°~+105°C
 Wire Size Flat Cable I.D.C: 1.27mm Pitch
 AWG#28(standard) OR #30 (solid).
 Material And Finish
 Insulator:PBT&Glass-fiber reinforced UL94V-0
 Insulator Color:Black
 Contact:Phosphor Bronze or Brass
 Contact Plating:See Contact Plating Tab.
 Note:(*)Marked is Important DIM For QC.
 PCB THICKNESS: 1.6MM

No. of Positions

No.	A	B	C
10	22.36	10.16	11.43
14	27.44	15.24	16.51
16	29.98	17.78	19.05
20	35.06	22.86	24.13
26	42.68	30.48	31.75
34	52.84	40.64	41.91
40	60.46	48.26	49.53
50	73.16	60.96	62.23

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	GENERAL ANGLE X ± 0.35 X' ± 5.0° XX ± 0.25 X" ± 3.0° XXX ± 0.10 XXX' ± 2.0°	PART NAME 品名 2.54MM EDGE CARD CONNECTOR IDC TYPE XXP SELECTIVE GOLD PLATING BLACK INSULATOR ROHS
DATE 制表日 2016/03/25	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C2900-XXXXSB00R
	PAGE 張數 1 OF 1	REV. 版次 A	