



Material:

Insulator: PBT, Glass Fiber (UL94V-0).

Contact: Brass. Selective Gold Flash Over Nickel.

Specification:

Current Rating: 1A AC, DC

Voltage Rating: 250V AC, DC.

Operating Temp: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$.

Insulation Resistance: $1000\text{M}\Omega$ min.

Dielectric Withstanding Voltage: 500V AC 1 min.

Contact Resistance: $20\text{m}\Omega$ max.

RoHS Compliant		HSM 玄茂科技股份有限公司	
		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		UNLESS OTHERWISE SPECIFIED TOLERANCE: X ± 0.2 ANGLES: ± 2° XX ± 0.1 XXX ± 0.05 DO NOT SEAL DRAWING	PART NAME 品名 IDC SOCKET 2.54mm X 2.54mm XXPIN W/ SPRING LATCH WITH BUMP BLACK INSULATOR ROHS
DWG. 製圖	Betty	SCALE 比例 參考	PART NO. C3001-XXLYXB00R
DATE 制表日	2017/01/12	UNIT 單位 MM	料號
		PAGE 張數 1 OF 1	
		REV. 版次 A	