



MATERIALS:

- 1. HOUSING: PBT (UL 94V-0) BLACK
- 2. TERMINAL: COPPER ALLOY GOLD FLASH PLATING ON CONTACT AREA UNDER PLATING NICKEL. (t=0.30mm)

SPECIFICATION:

- 1. CURRENT RATING: 1 AMP. MAX.
- 2. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC P.M.S. FOR ONE MINUTE.
- 3. INSULATION RESISTANDING: 500M OHMS MIN. AT 500V DC
- 4. CONTACT RESISTANCE: 30m OHMS MAX.
- 5. OPERATING TEMPERATURE: -40°C TO +85°C.

100	63.60	62.865	68.40	68.40
80	50.90	50.165	55.70	55.70
68	43.28	42.545	48.08	48.08
60	38.20	37.465	43.00	43.00
50	31.85	31.115	36.65	36.65
44	28.04	27.305	32.84	32.84
40	25.50	24.765	30.30	30.30
34	21.69	20.955	26.49	26.49
30	19.15	18.415	23.95	23.95
26	16.61	15.875	21.41	21.41
22	14.07	13.335	18.87	18.87
20	12.80	12.065	17.60	17.60
16	10.26	9.525	15.06	15.06
14	8.99	8.255	13.79	13.79
10	6.45	5.715	11.25	11.25
PIN	A	B	C	D
尺寸				

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准
BETTY

DWG.
製圖
BETTY

DATE 制表日
2011/06/16

SCALE
比例 參考

UNIT
單位 M M

PAGE
張數 1 OF 1

TOLERANCE:
X. ±0.30
.X ±0.20
.XX ±0.10
.XXX ±0.03

SIZE.
紙張尺寸 A 4

REV.
版次 B

PART NAME 品名
IDC SOCKET H.D. 1.27mm B TYPE XXP
WITH BUMP SELECTIVE GOLD PLATING
BLACK COLOR ROHS

PART NO.
料號 C3007-XXXYSB00R