



SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Brass

Contact plating (option):

⊖ G ⊖ Gold flash plating: Gold plating 0.6u ⊖ over Nickel plating 30u ⊖ ;

⊖ S ⊖ Selective gold plating: Contact area Gold plating 0.6u ⊖

, Solder area Tin plating 60u ⊖ over Nickel plating 30u ⊖

Electrical

Current Rating : 2 Amp

Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C



POSITION	A	B	C	D
6	15.28	12.42	5.08	2.30
8	17.82	14.96	7.62	2.30
10	20.36	17.50	10.16	5.00
12	22.90	20.04	12.70	5.00
14	25.44	22.58	15.24	5.00
16	27.98	25.12	17.78	5.00
20	33.06	30.20	22.86	5.00
24	38.14	35.28	27.94	5.00
26	40.68	37.82	30.48	5.00
30	45.76	42.90	35.56	5.00
34	50.84	47.98	40.64	5.00
40	58.46	55.60	48.26	5.00
50	71.16	68.30	60.96	5.00
60	83.86	81.00	73.66	5.00
64	88.94	86.08	78.74	5.00

ACCESSORIES	X	Y
LONG LATCH	22.1	14.6
SHORT LATCH	18.7	10.6

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准</p>	<p>TOLERANCE 容許公差</p> <p>.0 ± 0.30</p> <p>.00 ± 0.20</p> <p>ANG. ± 3°</p>	<p>PART NAME 品名</p> <p>2.54mm X 2.54mm SHROUDED HEADER WITH PLASTIC EJECTOR 2XXXP STRAIGHT TYPE BLACK INSULATOR ROHS</p>	
<p>DWG. 製圖</p> <p>Betty</p>	<p>SCALE 比例 參考</p> <p>UNIT 單位 M M</p> <p>PAGE 張數 1 OF 1</p>	<p>SIZE 紙張尺寸 A 4</p>	<p>PART NO. 料號</p> <p>C3011-XXSXXB00R</p>
<p>DATE 制表日</p> <p>2015/10/30</p>		<p>REV. 版次</p> <p>A</p>	