



Current Rating Voltage: 3 Amps 250V AC (r.m.s)
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max.
 Dielectric Withstanding: 1000 V AC
 Operating Temperature: - 40° ~ +105° C
 Contact Material: Copper Alloy
 Standard: Brass
 Insulator Material: Polyester, UL 94V-0
 Standard: PBT
 Max Processing Temp: 230° C for 60 seconds

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 .X ±0.3 .XX ±0.20 .XXX ±0.100	PART NAME 品名 BOX HEADER+PIN HEADER 2.54MM X 2.54MM 2XXXPIN STRAIGHT TYPE MATTE (A=9.1MM C=7.1MM B=2.3MM) MATERIAL: PBT UL94V-0 BOX PACKING ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	
DATE 制表日 2023/12/07	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C3521-XXSL2XBPD0R