


RoHS Compliant		HSM 玄茂科技股份有限公司	
		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	HELEN	TOLERANCE LINEAR: X ±0.50, .X ±0.30, .XX ±0.20, .XXX ±0.10 ANGLES: X° ±2.0°, .X° ±1.0°, .XX° ±, .XXX° ±	PART NAME 品名
DWG. 製圖	ABBY		0.8mm MINI PCI EXPRESS SOCKET 52PIN SMT 90° H=4.0mm SELECTIVE GOLD PLATING BLACK INSULATOR REEL PACKING ROHS
DATE 制表日	2018/06/12	SCALE 比例 參考	PART NO. 料號
		UNIT 單位 M M	C3618-52ASBR00R
		PAGE 張數 1 OF 2	
		REV. 版次 A	



**NOTES:**

1. **Material:**
  - Housing: LCP High Temperature Thermoplastic, UL 94V-0;
  - Terminal: Copper Alloy;
  - PEG: Copper Alloy;
2. **Electrical characteristics:**
  - a. Voltage rating: 50V AC per contact;
  - b. Current rating: 0.5 AMP per contact;
  - c. Dielectric withstanding voltage: 300V AC RMS (Min);
  - d. Insulation resistance: 500 Megohms at 500V DC Min;
  - e. Contact resistance: 55 milliohms Max (initial);
3. **Mechanical characteristics:**
  - a. Insertion force: 2.3kgf Max;
  - b. Withdrawal force: 2.3kgf Max;
  - c. Durability: insert & withdraw 50 cycles;

RoHS Compliant	<b>HSM</b> 玄茂科技股份有限公司	<b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	HELEN	SCALE 比例	TOLERANCE LINEAR ANGLES X ±0.50 X' ±2.0° .X ±0.30 .X' ±1.0° .XX ±0.20 .XX' ± .XXX ±0.10 .XXX' ±
DWG. 製圖	ABBY	UNIT 單位	SIZE 紙張尺寸
DATE 制表日	2018/06/12	PAGE 張數	REV. 版次
		2 OF 2	A 4
		A	
		PART NAME 品名 0.8mm MINI PCI EXPRESS SOCKET 52PIN SMT 90° H=4.0mm SELECTIVE GOLD PLATING BLACK INSULATOR REEL PACKING ROHS	
		PART NO. 料號 C3618-52ASBR00R	