



SECTION: A-A

PIN數	A	B	C
36	7.65	6.00	25.00
64	21.65	20.00	39.00
98	38.65	37.00	56.00
164	71.65	70.00	89.00

Note:

- 1:Electvical Performance
  - 1.1.Dielectric Withstanding Voltabge: 500V/AC For 1.0 Minute.
  - 1.2.Contadt Resistance:30mΩ Max
  - 1.3.linsulation Resistance:1000MΩ Min
- 2.Mechanical Performance.
  - 2.1.CONTACT INSERTION FORCE: 0.115Kg Max Per.Contact Pair.
  - 2.2.CONTACT WITHDRAWAL FORCE: 0.015Kg Min Per.Contact Pair.
  - 2.3.Terminal Retention Force (in housing): 0.5Kg Minper Terminal.
- 3.Material & Finish:
  - 3.1.Housing: Glass Filled Nylon 66, Black.
  - 3.2.Contact Plating: Tin Plating At Solder Tail Area;  
Gold Plating At Mating Area, All Over Nickel Plating.
- 4.Environmental:Operating Temperature: -55°C~+85°C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN		METRIC TOLERANCE .0 ±0.20 .00 ±0.10 .000 ±0.001 .0000 ±0.0001 ANG ±.3°	PART NAME 品名 1.0mm PCI Express Straddle Type Without Ear XXPin Insulator Material:Nylon 66 Terminal:Brss Selective Gold Plating Tube Packing ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2020/09/09	PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 C3620-XXABSBT0R