



PIN數	A	B	C	D
36	7.65	6.00	25.00	9.30
64	21.65	20.00	39.00	23.30
98	38.65	37.00	56.00	40.30
164	71.65	70.00	89.00	73.30

- Note:
- Electrical Performance
 - Dielectric Withstanding Voltage: 500V/AC For 1.0 Minute.
 - Contact Resistance: 30mΩ Max
 - Insulation Resistance: 1000MΩ Min
 - Mechanical Performance.
 - CONTACT INSERTION FORCE: 0.115Kg Max Per.Contact Pair.
 - CONTACT WITHDRAWAL FORCE: 0.015Kg Min Per.Contact Pair.
 - Terminal Retention Force (in housing): 0.5Kg Min per Terminal.
 - Material & Finish:
 - Insulator: Hi-Temp NY-9T UL 94V-0, 260°/10Sec, Black
 - Contact Plating: Tin Plating At Solder Tail Area; Gold Plating At Mating Area, All Over Nickel Plating.
 - Environmental: Operating Temperature: -55°C~+85°C

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE METRIC TOLERANCE .0 ±0.20 .00 ±0.10 .000 ±0.001 .0000 ±.03 ANG	PART NAME 品名 1.0mm PCI EXPRESS SMT TYPE XXPIN PLASTIC POSTS BODY MATERIAL: NY 9T CONTACT MATERIAL: BRASS SELECTIVE GOLD BLACK INSULATOR ROHS
DWG. 製圖 Betty		SIZE. 紙張尺寸 A 4	PART NO. 料號 C3621-XXPBBSBTR
DATE 制表日 2019/03/26		REV. 版次 A	