



Electrical properties

- 1 `Current rating:1A AC\DC
- 2 `Voltage rating: 250V AC\DC
- 3 `Temperature range: -25℃ to 85℃
- 4 `Contact resistance:Initial value/30mΩ max
- 5 `Insulation resistance:60MΩ min
- 6 `Withstanding voltage:500V AC/ minute

Environmental controls

- 1 `Banned contains SS - 00259 are restricted substances.
- 2 `The corresponding issued by SGS or ITS icp-aes data, Not the material in a list, and validity.

Bronze	Tin Plating : 80u"~200u"
Plastic	LCP i130 Natural
MATERIAL	FINISH

APPD. 核准 DWG. 製圖 DATE 制表日 2019/06/13	Betty		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
		SCALE 比例 參考	TOLERANCE .X: ±0.1 .X': ±1.5 .XX: ±0.05 .X': ±1.0 .XXX: ±0.03 .X': ±0.5	PART NAME 品名 2.5mm LED CONNECTOR 2PIN RIGHT ANGLE TYPE (C=11.5mm D=2.5mm) MATERIAL:PHOSPHOR BRONZE TIN PLATING WITH LOCATING PEG BAG PACKING BEIGE COLOR (MATERIAL:LCP) ROHS	
		UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C3803-02RTPARGR	
		PAGE 張數 1 OF 1	REV. 版次 A		

P.C.B